

www.continentalflooring.com info@continentalflooring.com 800-825-1221

Duo Luxury Vinyl Tile



ArmstrongFlooring




Sand, Si bil Mixer 2, Champagne, Si bi6 Mixer 2, xer 2, Blue Hawaiian, ST524 Mixer 2, Blue Lagoon, ST529 Mixer 2, Zinfandel

Embrace a spectrum of color with **Mixer 2**. Available in 6 in. x 36 in. planks, Mixer 2 offers 16 saturated colorways with a soft background texture to create a tie-dye inspired look.





The **Spettro** design captures textural and visual softness in neutral colorways and is available in two sizes: 18 in. x 36 in. tiles and 6 in. x 36 in. planks.





ST931 Spettro, Caspian Sand



ST932 Spettro, English Grey



ST2PR Spettro, English Grey with Mixer 2, Blue Hawaiian and Blue Lagoon



ST933 Spettro, Nile Night

Product Information

Construction - Solid Vinyl Tile (Luxury Vinyl Tile / LVT)

International Specifications - ASTM F 1700, Class III, Type B embossed surface

Overall Thickness - 0.100 in. (2.5 mm)

Wear Layer Thickness - 0.0020 in. (0.5 mm)

Factory Finish - Diamond 10® Technology

Installation - Adhesives: S-995, S-319 Roll Strong™, S-1000 Maintenance Options - No Polish - No Buff, Polish Optional

Packaging

Size

Pieces per Carton/Coverage

6 in. x 36 in. (152 mm x 914 mm) 18 in. x 36 in. (457 mm x 914 mm) 24 / (36 sq. ft.) 5.02 m² 12 / (54 sq. ft.) 5.02 m²



www.continentalflooring.com info@continentalflooring.com 800-825-1221



ST932 Spettro, English Grey



1. Diamond 10® Technology

Patented innovation that uses cultured diamonds to provide category-leading scratch, stain, and scuff resistance from edge-to-edge

2. Rigid Wear Layer

The combination of Diamond 10® Technology and the unique rigid wear layer results in enhanced durability and abrasion resistance

- 3. Realistic Printed Visual
- 4. Foundation Layer

5. Eased Edge

Designed to blend seamlessly into the next plank for ease of maintenance and cleanability

20 Year Commercial Limited Warranty

Supported by a 20 Year Commercial Limited Warranty. Add 10 years of overall warranty coverage by using Strong System™ subfloor preparation products. Visit ArmstrongFlooring.com for more information.