



www.continentalflooring.com
 info@continentalflooring.com
 800-825-1221

Safety Zone Vinyl Tile



ArmstrongFlooring



Safety Zone™ Tile

is made with an embossed surface embedded with proprietary particles for exceptional slip-retardant performance, with colors and patterns that provide hiding power against scuffs, scratches, and abrasion. No specialized maintenance required; follow traditional VCT maintenance protocols including the application of polish and periodic restorative maintenance.

Product Information

Construction - Vinyl Composition Tile

International Specifications - ASTM F1066 - Class 2 Through Pattern

Overall/Wear Layer Thickness - 1/8 in. (3.2 mm)

Factory Finish - Fast Start®

Installation - Adhesives: S-515, S-525

Maintenance Options - Polish

- Fast Start® Factory Finish protects the tile during installation and makes initial maintenance quick and easy.
- Features through-pattern wear layer for lasting performance, even under heavy traffic conditions.
- Available in 12" x 12" format for modular flexibility.

Packaging

Size

12 in. x 12 in. (305 mm x 305 mm)

Pieces per Carton/Coverage

12 in. x 12 in. - 12 (45 sq. ft.) 4.18 m²

Shipping Weight per Carton

63 lbs. (28.6 kg)

57016
vanilla bean



57021
neapolitan




57023
salt water taffy



57017
cookie dough



57000
earth stone




57001
shale gray




57018
butter pecan



57020
blueberry swirl



57022
rocky road



57019
salted caramel



57008
soft cedar



57004
slate black

